



## **CONCRETE FLOOR & CRACK REPAIR KIT**

### **Easy To Use One Step Permanent Repair Process**

- Repairs Cracks, Joints, & Pot Holes
- No special preparation, work, or priming
- Cures at room temp in 30 minutes
- Cures in sub zero temp in 60-90min
- Pre-mixed & ready to use
- Excellent on expansion joints
- No shrinking or peeling
- No heat systems or lamps required
- Use on dry or damp floors
- From 12" deep to feather edging at 1-16"
- Use Indoors or Outdoors

**FOR PROFESSIONAL USE ONLY**  
CONSULT LABEL AND MSDS BEFORE USING.

#### **Many Uses Including:**

Warehouse & Building Floors  
Expansion joints  
Loading Docks  
Freezers & Freezer Walls  
Thresholds of Coolers  
Re-built Drains  
Parking lots  
Dry or Damp Areas

## **CONCRETE FLOOR & CRACK REPAIR KIT**

### **EZ TO USE ONE STEP PERMANENT REPAIR PROCESS**

This concrete repair is stronger than concrete with the same bulk density and sets up in a fraction of the time for minimal downtime and traffic interruption. It's easy to mix and apply, requires no special personnel or equipment. Can be feathered for smooth and strong bond to concrete. It creates a permanent bond so the repair becomes part of the structure. Does not



shatter; excellent for anchoring machinery and vibrating equipment as well as cracks.

In cracks, both large and small, and any type of concrete foundations that are serious. They can become wider and lead to major types of

repairs or lead to water seepage, and are dangerous in manufacturing and warehouse areas, since they cause unsafe effects for vehicles and forklifts.

This is a unique polyester repair kit that contains only 2 components. 40lbs of special powder or aggregate + 1 gallon of liquid polyester. While traditionally Epoxies have been used, polyester is different, in that it hardens 3 times harder than cement, fills any size crack or hole, and hardens in 30 minutes. Plants and operations no longer have to make a repair. Preparation of the area is easy. Just clean with a degreaser, Superco "Hurricane".

#### **Directions For Use: Concrete floor & Crack Repair Kit**

There are 2 components:

1. 40lbs Powder & a 1 Gallon can of Polyester Liquid.
2. Spill off about 1/4 of the liquid into a separate container, add catalyst, then apply right away.
3. Mix up some more if needed.

#### **Additional information**

Concrete Floor & Crack Repair Kit is a material that is stronger than concrete and has the same bulk density. Use Concrete Floor & Crack Repair Kit to repair damage caused to warehouse floors, building floors, thresholds of coolers, parking lots, dry or damp areas etc... It does so by filling any size crack or hole. It hardens to create a permanent bond with the concrete. This causes the repair to become apart of the structure. Use SUPERCO'S HURRICANE (degreaser) during the preparation process to clean the area. Follow that by using CONCRETE FLOOR & CRACK REPAIR KIT.

**SUPERCO SPECIALTY PRODUCTS**

VISIT OUR WEBSITE - [www.supercoproducts.com](http://www.supercoproducts.com) • Call Toll-Free (800)320-0102 • FAX (661)775-8884