



EX-PAND A

EXPANDABLE INSULATING FOAM SEALANT

- FILLS HOLES (SEALS OUT PESTS)
- STOPS DIRT AND DRAFTS
- DAMPENS SOUND

1" THICKNESS YIELDS R-5
INSULATING FACTOR

PRODUCT #1108

**FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.**

EX-PAND A EXPANDABLE FOAM SEALANT ' EASY TO USE ' CONFORMS TO ANY SHAPE

EX-PAND is an unique one part urethane foam which expands as it dries and solidifies. **EX-PAND A** fills cracks and holes that caulk can't. Sprays as a liquid then expands and cures to a durable semi-rigid closed cell foam insulation. **EX-PAND A** conforms to any shape to form a water resistant, weather resistant and airtight bond on masonry, wood, metal, glass, tile and most plastics.

SURFACE PREPARATION AND USE:

PLEASE NOTE: As with any handling of chemicals precautions must be used when handling **EX-PAND A**. Gloves and eye protection should be worn during use. Use only in well ventilated areas.



Clean surface and surrounding area. Remove loose dirt, debris, oil and grease from surface. Protect work area with a drop cloth or newspaper. Mask adjacent areas with tape, paper or poly film.

Shake can vigorously for one minute prior to use. Press extension tube firmly onto plastic trigger actuator. Invert can and press trigger slowly. Do not fill cavity completely full!! Fill cavity only 40% as product will expand 200-300%. Release trigger 5 seconds before desired end point. Clean up any unwanted uncured foam immediately with either paint thinner or acetone. Any cured foam must be cut off or sanded. Cured foam may be painted. Remainder of can must be used in 30 days. Cut off 1 inch of extender tube for reuse.

1	HEALTH
1	FLAMMABILITY
1	REACTIVITY
	PERSONAL

INGREDIENTS	CAS NUMBER
POLYMERIC DIPHENYLMETHANE DIISOCYANATE	101-68-8
HIGHER OLIGOMERS OF MDI	9016-87-9
HYDROFLUOROALKANE	
PHTHALATE ESTER	85-68-7
POLYOL	N/E
FLAME RETARDENT	N/E
CATALYST	N/E

Additional Information

EX-PAND A is a highly expanding poly-foam filler and sealant. Fill holes or gaps in walls and floors easily with **EX-PAND A** then trim away excess, sand, then paint or stain to match. Filling these gaps and holes can prevent rodents and insects from travelling from room to room thus making pest control easier and more effective. Gaps in walls and floors can allow fire to spread more rapidly by allowing air to flow into consumed areas. Use **EX-PAND A** to soundproof around appliances, machinery, etc. anywhere excessive noise is a problem. **EX-PAND A** has excellent adhesive power. Use in areas where other glues have failed. **EX-PAND A** bonds, weatherproofs and soundproofs all in one step. Troubled by rattles and vibrations that cause irritating noise? Use **EX-PAND A** inside, behind, under and around these areas to eliminate rattles and noises. **EX-PAND A** may be the most versatile product you have ever used.

SUPERCO SPECIALTY PRODUCTS