



F-O-U-R WAY

**NON-FLAMMABLE
FASTENER LOOSENER**

**Penetrates, Lubricates
Displaces Moisture**

**FREES FROZEN
NUTS & BOLTS**

- Non-Conductive
- Non-Chlorinated
- Dielectric Strength Rating to 30,000 Volts

VOC COMPLIANT IN ALL 50 STATES

Product: #1714

**FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.**



F-O-U-R WAY NON-FLAMMABLE FASTENER LOOSENER

Spray area to be treated an let **F-O-U-R WAY** penetrate in between rusted or seized parts. This fast acting formula will loosen threads, tightly fitted parts, sliding and rotating parts, bolts, hinges and pins that have been "frozen" by corrosion. **F-O-U-R WAY** will protect against renewed corrosion, is a powerful, multi-action protective shield against effects of moisture and corrosion. **F-O-U-R WAY** will protect electrical gear, metal and other surfaces with a complete molecular film. **F-O-U-R WAY** will preserve equipment reducing repair and maintenance costs. **F-O-U-R WAY** will lubricate, loosen dirt, scale and other corrosive elements, while never becoming dry, brittle or hard. **F-O-U-R WAY** can also be used on wet or dry surfaces. The conductivity of commutators and contacts is protected with using **F-O-U-R WAY**.

USES:

Loosening Fasteners, Locks, Hinges, Battery Terminals, Auto & Truck Repair, Alternators, Starters, Cranes, Elevators, Parking Meters, Equipment, Farm Equipment, Aerospace Equipment, Bronze, Hospital Beds, Airplanes, Aluminum, Steel, Iron, Copper, Ceramics, High Voltage Equipment.

DIRECTIONS:

Spray **F-O-U-R WAY** liberally, directly on area to be treated. Reapply periodically as required. To ensure adequate protection, periodic checks should be made to determine the need to replication.

INGREDIENTS

ISOPARAFINIC HYDROCARBON
MINERAL OIL
OCTAMETHYLCYCLETETRASIOXANE
DIPROPYLENE GLYCOL MONOMETHYL ETHER
CARBON DIOXIDE

CAS NUMBER

64742-47-8
8042-47-5
556-67-2
34590-94-8
124-38-9

1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
A	PERSONAL

Additional Information

F-O-U-R WAY will loosen dirt and scale from painted and plated surfaces. Removes loosened scale and spray again to cover surface. Liberal application will loosen threads, tightly fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. **F-O-U-R WAY's** formula will protect against renewed corrosion. **F-O-U-R WAY** is a powerful, multi-action protective shield against the harmful effects of moisture and corrosion. It will protect electrical gear, metal and other surfaces from deterioration by displacing water and moisture and sealing all surfaces with a complete molecular film. **F-O-U-R WAY** preserves equipment, thus reducing repair and maintenance costs. **F-O-U-R WAY** also lubricates, never becomes dry, brittle or hard. **F-O-U-R WAY** protects the properties of insulating substances. Ask your **Superco Specialty Products** representative to demonstrate **F-O-U-R WAY** as well as our many remarkable products.

SUPERCO SPECIALTY PRODUCTS

VISIT OUR WEBSITE - www.supercoproducts.com • Call Toll-Free (800)320-0102 • FAX (661)775-8884