

The YES Company!!



FIBER KOTE
All Weather Roof Cement

- FORMS ITS OWN MEMBRANE
- HEAVILY FIBERIZED FOR EXTREME DURABILITY
- GLASS FIBER REINFORCED
- REMAINS SOFT AND PLIABLE LONGER THAN OTHER SIMILAR CEMENTS
- WILL NOT SAG OR RUN IN HOT WEATHER
- REPAIRS CRACKS, BULGES, BLISTERS & OPEN SEAMS

Product # 7033

FOR PROFESSIONAL USE ONLY
 CONSULT LABEL AND MSDS BEFORE USING.

INGREDIENTS
 MINERAL SPIRITS

CAS NUMBER
 8052-41-3

1	HEALTH
2	FLAMMABILITY
1	REACTIVITY
	PROTECTION

FIBER KOTE

All Weather Roof Cement

FIBER KOTE Roof Cement is unique in several respects. It contains fiber strands for reinforcement, so that no other reinforcing membrane or sheet is required when patching with this compound. It is specially formulated to be readily used in cold as well as hot weather, and over damp or wet surfaces. **FIBER KOTE** is plasticized to give outstanding durability. This is truly a premium grade product.

FIBER KOTE is used for all repairs and for stopping roof leaks. Use for the construction and repair of flashings. **FIBER KOTE** All Weather Roof Cement stops leaks around vent pipes, spouts, valleys, skylights, gutters and chimneys. It may be used to seal cracks in chimneys, walls and foundation joints, for lining leaking gutters and troughs.

DIRECTIONS FOR USE:

Surface Preparation: Remove dust, dirt and debris using a stiff brush or broom. Remove crusted rust or scaling previous coating by scraping or wire brushing.

On Composition Roofs: Replace all drawn up nails before patching. If roof is dried out, apply primer before patching with roof cement. **ON CONCRETE ROOFS:** Always apply primer before patching with **FIBER KOTE**. **ON METAL ROOFS:** Always re nail loose laps before patching with **FIBER KOTE**.

ADHERES TO BOTH WET & DRY SURFACES.

Applies easily in either hot or cold weather.

Application: Apply with trowel or putty knife. Occasionally dipping trowel in paint thinner will reduce sticking. **TO PATCH HOLES OR BREAKS:** Fill with plastic cement and smooth down edges. Apply **FIBER KOTE** at least ¼" thick. No saturated glass or cotton membrane, aluminum foil, roofing paper or metal support is needed for **FIBER KOTE**. For easiest workability during cold weather, keep this material in a heated room before using. One gallon covers approximately 6-7 sq. feet at ¼" thick.

Add ition al Inf or mation

FIBER KOTE All Weather Roof Cement is probably the best, most durable and long lasting roof patching compound made today. This remarkable formula can be used on wet or dry surfaces, even under standing water. **FIBER KOTE** will not freeze in the winter or melt in the summer heat and stays permanently flexible. The Canadian fiber reinforcing this product forms its own membrane so no other sheets or films are needed to form a long lasting seal. Use **FIBER KOTE** as an adhesive, sealer, roof mastic and repair product. Contact your local **SUPERCO SPECIALTY PRODUCTS** representative for a demonstration.