

The YES Company!!



FORMULA 30
Tar & Asphalt Remover
Engine Degreaser

- GEL FORMULA CLINGS TO VERTICAL SURFACES
- EMULSIFIES GREASE AND TAR
- USE ON HEAVY EQUIPMENT

Product # 5006 Bulk

FOR PROFESSIONAL USE ONLY
 CONSULT LABEL AND MSDS BEFORE USING.

BULK INGREDIENTS	CAS NUMBER
METHYLENE CHLORIDE	75-09-2
PERCHLOROETHYLENE	127-18-4
ALIPHATIC HYDROCARBONS	64-742-7

1	HEALTH
2	FLAMMABILITY
1	REACTIVITY
	SPECIFIC

FORMULA 30

Tar and Asphalt Remover

FORMULA 30 Engine Degreaser effectively removes grease, tar, asphalt, oil stains and dirt from engines, industrial equipment, concrete, ceilings, vertical surfaces, industrial machinery and metal parts. Gel formulation will not run, giving deep penetration for complete cleaning. Emulsifies tar, asphalt, baseboard cements, oils, grease and asphalt base roofing compounds. Easy to use; Just spray on and wash off with water. Authorized by the USDA for use in meat and poultry processing plants.

DIRECTIONS FOR USE:

When using on painted surfaces, pre-test a small area to be sure paint is not affected. Apply a thorough coating, being sure to cover all grease, oil or tar.

For Engines: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes for complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.

Other Surfaces: To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for a few minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

Additional Information

FORMULA 30 Tar and Asphalt Remover is a powerful formula for dissolving and removing the toughest type of grease which is tar and asphalt. **FORMULA 30's** unique gel formulation clings to equipment and vertical surfaces to increase cleaning power. Excellent for removing road tar and oil from paving equipment and vehicles. Strong enough to dissolve asphalt based roofing materials, glues, tree sap, etc. Use to clean up tools and equipment used for paving and roofing. **FORMULA 30** is great for degreasing engines and transmissions. Spray **FORMULA 30** on equipment before pressure washing to remove any caked-on grease that otherwise would not come off with pressure alone. **FORMULA 30** is a good option to using chlorinated solvents.