The YES Company!!
SUPERCO SPECIALTY PRODUCTS

ICE-MELT

ICE AND SNOW MELTER

- CONTAINS NO SALTS, ALKALIS, OR ACIDS.
- WILL NOT HARM CARPETS, PAINTS, FINISHES, GRASS, OR CONCRETE.
- USE ON: SIDEWALKS, AUTO AND TRUCK SURFACES, WALKWAYS, DRIVEWAYS, SIDEWALKS, WINDOWS, AND WINDSHIELDS.

PRODUCT:
 # 1103 AEROSOL
 # 5178 BULK LIQUID
 # 7070 50LB GRANULAR

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

AEROSOL	
4	HEALTH
4	FLAMMABILITY
0	REACTIVITY
	PROTECTION

LIQUID	
2	HEALTH
3	FLAMMABILITY
0	REACTIVITY
B	PROTECTION

GRANULAR	
0	HEALTH
0	FLAMMABILITY
0	REACTIVITY
	PROTECTION

AEROSOL INGREDIENTS	CAS #
METHANOL	67-56-1
ETHYLENE GLYCOL	107-21-1
BULK LIQUID INGREDIENTS	**CAS #**
ISOPROPYL ALCOHOL	67-63-0
GRANULAR INGREDIENTS	**CAS #**

CONTAINS NO HAZARDOUS COMPONENTS AS DEFINED IN 29 CFR 1910, 1200 (d)

ICE-MELT

ICE-MELT ready to use ice melting compound is formulated to work by azeotropic action. No heat is generated, no harsh corrosive salts to destroy concrete surfaces or harm lawns, no waiting. This compound chemically unites with ice or snow and changes the normal freezing point thus preventing adhesion onto surfaces. Pretreated surfaces may be swept clean of ice or snow. New formulations of ice or snow may be removed by treating with ***ICE-MELT***. Use ***ICE-MELT AEROSOL*** on frozen locks and windshields without damaging paint or finishes.

DIRECTIONS FOR USE:

Liquids: For most uniform coverage, use a Hudson type pump-up sprayer or a compressed air sprayer, which has been adjusted to a stream type spray pattern.

On Flat Surfaces and Walkways: Score ice with a rake to enable deeper, faster penetration into ice formations. Spray product onto surface at a rate of 1 gallon per 550 square feet for removal.

On Windows, Windshields, or Automotive Surfaces: Spray onto surface according to coverage rates listed above. Cover surface with spray, allow a few minutes for melting to occur, then wipe away ice layer.

Granular: Before using be sure to shovel or plow away excess snow, and apply only to the remaining, hard packed snow. Spread **ICE MELT** pellets at the rate of ¼ pound per square yard. Do not overspread. Be sure that **ICE MELT** is spread evenly and that there are no piles.

ICE MELT should not be use on concrete less than one year old and should not be used on concrete with exposed aggregate, precast steps. Should not be used on chipped or cracked concrete, or brick steps or walks.

Additional Information

In tests conducted by a leading independent research laboratory comparing ***ICE-MELT*** with **MG-104** (granular) and a calcium chloride based ice melter, ***ICE-MELT*** penetrated ice deeper over a period of two hours. In addition, at colder temperatures, ***ICE-MELT*** was found, hours after application, to prevent ice reformation where the calcium chloride product did not. In further laboratory testing, with frozen distilled water, ***ICE-MELT*** penetrated through and dislodged the ice where the calcium chloride ice melt product did not, indicating ***ICE-MELT***'s superior ability to break the ice bond to a hard surface. In tests at temperatures ranging from -6° F to 5° F, when calcium chloride treated ice began to re-freeze, ice treated with ***ICE-MELT*** continued to melt up to 2½ times longer. For more information or a demonstration on the effectiveness of ***ICE-MELT*** please contact your local ***SUPERCO*** sales representative.

SUPERCO SPECIALTY PRODUCTS
VISIT OUR WEBSITE - www.supercoproducts.com • Call Toll-Free (800)320-0102 • FAX (661)775-8884