

The YES Company!!

**SUPERCO**  
SPECIALTY PRODUCTS

**LIFT STATION  
PURE**  
DEGREASES, DEODORIZES, AND CLEANS

- CONTAINS SOY BEAN OIL, NATURAL CORN SURFACTANTS AND d-LIMONENE
- USE IN LIFT STATIONS, GREASE TRAPS, DRAIN LINES, SUMPS, PORTABLE TOILETS, SEWAGE PITS
- 100% NATURAL & BIODEGRADABLE
- WILL NOT INTERFERE WITH BIOLOGICAL DIGESTION OF BACTERIA AND ENZYMES
- LESS EVAPORATION THAN SOLVENT TYPE PRODUCTS
- STAYS ON SURFACE LONGER TO DIGEST FATS AND GREASE AND REMOVE HEAVY DEPOSITS

PRODUCT #5123 BULK

**FOR PROFESSIONAL USE ONLY**  
CONSULT LABEL AND MSDS BEFORE USING.

**LIFT STATION  
PURE**

DEGREASES, DEODORIZES, AND CLEANS

PURE LIFT STATION emulsifies and degreases raw sewage as it floats into lift station wells. The accumulation of sewage, grease, oils, fatty acids, calcium, and soap scum form deposits on wet well walls. **PURE LIFT STATION**, by nature's own power, liquefies and attacks the grease so it flows away. **PURE LIFT STATION** leaves a pleasant light citrus scent that effectively controls offensive odors.



Add **PURE LIFT STATION** directly to lift station wet wells in its concentrated form for effortless cleaning. Degreasing and cleaning is accomplished by the rise and fall of the water level. As the water level rises and lowers, **PURE LIFT STATION** removes the sludge from the sides of the walls, then "seals and contains" offensive odors from the lift station and totally eliminates the offensive job of cleaning lift station grease traps or sumps manually.

**PURE LIFT STATION** is biodegradable, non-freezing, contains no phosphates, no quaternary compounds, no chlorinated solvents, and is free from alkali and acids and will not inhibit waste digestion when used as directed.

**DIRECTIONS FOR USE:**

**PURE LIFT STATION** should be added to wet well until a layer of 8 to 12 inches is floating on the surface. This initial treatment should remain effective for a period of 3 to 6 months, depending on system demands. Add as needed. **FOR LIFT STATION CLEANING AND DEGREASING:** To start, add enough product to get a 5 - 7 inch base on top of the lift station. Add 2 - 3 gallons

directly to area on a bi-weekly basis to keep up the level at 5 - 7 inches

**Ingredients**

Soy Methyl Ester  
Nonylphenoxypolyethoxyethanol  
D-limonene

**CAS#**

N/E  
9016-45-9  
5989-27-5

HMIS	
0	HEALTH
1	FLAMMABILITY
0	REACTIVITY
	PERSONAL

**Additional Information**

Cleaning lift stations, wet wells, sumps, and grease traps is by far one of the most time consuming and offensive jobs. Then add to that, the fact that these areas get dirty and grimy more frequently, in fact, immediately. In today's world of lean maintenance crews who has time (or the desire) to maintain and clean lift stations and wet wells, anyway. **PURE LIFT STATION** is the perfect solution. Applied once every three to six months (or as needed), **PURE LIFT STATION** effectively cleans your traps, sumps, pits and wells constantly. This remarkable formula utilizes the rise and fall of the water level inside the pit or tank to emulsify grease and sludge while keeping the walls and sides clean. With **PURE LIFT STATION** at work you never have to get into your lift station to clean it or scrape-down the sides. Plus, no more complaints of bad odors coming up into elevator cars or out of vents because **PURE LIFT STATION** is a floating chemical that locks in any foul odors and leaves a smell of fresh oranges. **PURE LIFT STATION** is biodegradable and environmentally safe to meet your highest standards. We at **Superco Specialty Products** are doing our part as a responsible company to help protect our precious natural resources.