

The YES Company!!



SUPER LUBE

HIGH TEMP

HEAVY DUTY
HIGH TEMPERATURE
NON-MELT GREASE

- Resistant to: acids, water, salt spray, dirt, dust, steam, and oxidation
- Adhesive/Cohesive Properties
- Impact resistance
- Corrosion and rust inhibitor
- 65 Timken OK load
- Anti-wear Additives

Product # 7112 (bulk)
Product # 7050 (tubes)

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

SUPER-LUBE High Temp

High Temperature Multipurpose Grease

SUPER-LUBE High Temp is an all purpose non melt grease specially formulated with extreme pressure and antiwear additives to provide heavy duty service. It is one of very few greases able to withstand heavy shock load and impact pressures of 65 lb. Timken load capabilities. This product has excellent adhesive and cohesive properties. It resists most acids, weather, dirt, salts spray, steam and oxidation. Our product protects equipment indoors or outdoors even under high temperatures and heavy loads.



User Benefits:

- (1) Exceptional resistance to acids, water, salt-spray, weather, dirt, dust, steam and oxidation.
- (2) Exceptional adhesive-cohesive and antiwear properties.
- (3) Gives Extra "cushioning" that reduces shock and noise.
- (4) Performs at a wide variety of temperatures up to 550°F.
- (5) Excellent outdoor resistance, extreme pressure and high heat resistance. Water resistant too.
- (6) High Shock and impact resistance. No pound out or thin out.
- (7) Seals out dust, dirt and contaminants; prolongs life of metal parts.
- (8) Contains special corrosion and rust inhibitors.
- (9) Excellent load carrying capacity 65 lb. Timken load.

Typical Specifications:

Color:	Red
Penetration (ASTM D-217):	250-270
NLGI Grade:	1 and 2
Dropping Point (ASTM D-556):	+550°F (Non-Melt)
Timken OK Load (ASTM D-2509):	65 LB.
Water Resistance:	Excellent
Rust Resistance:	Excellent
Acid Resistance:	Excellent
USDA Category:	H2

CAS Numbers: Petroleum Distillate 8002059;
Rheological Thickeners 68953-58-2; N.J.#
800983-5015P.

HMIS RATING:
Health-1; Flammability-1; Reactivity- 0; Personal
Protection-B.

USES:

Automotive / Farms / Bottling Plants / Cotton Gins / Sugar Cane Mills / Dairies / Paper Mills / Industrial / Marine / Oil Fields / Steel Mills / Air Conditioning / Elevators / Textile Plants / Construction / Mining / Lumber Mills / Cement Plants / Food Plants / Sewage Plants.

Additional Information

SUPER LUBE HIGH TEMP is a non-melt grease that will perform at temperatures of up to 550° F. **SUPER LUBE HIGH TEMP's** exceptional adhesive/cohesive properties and anti-wear additives makes this grease ideal for high-rpm applications and more. **SUPER LUBE HIGH TEMP** will not wash, run, drip or fly out of bearings or fittings. **SUPER LUBE HIGH TEMP** is water-proof and serves as an effective barrier against dust, dirt and other harsh contaminants. Maintain the life of your equipment with this high quality grease and other's like it available now only at **SUPERCO SPECIALTY PRODUCTS**. Contact your local **SUPERCO** sales representative for more information on our exclusive line of quality lubricants.