



**ENVIRONMENTALLY FRIENDLY**  
**SAFE STRIP B**  
 Industrial Paint Stripper

Tough on Paint....Easy & safe on the Environment

- **NON FLAMMABLE/NON-HAZARDOUS**
- **BIODEGRADABLE - SAFE TO USE**
- **WATER BASED - EASY CLEAN UP**
- **REDUCES LABOR & DOWNTIME**
  - REDUCES POLLUTION
  - LOW ODOR

**USE AT:**

- **SCHOOL DISTRICTS**
- **MUNICIPALITIES**
- **CITIES**
- **PAINTING CREWS**
- **ROAD AND SIGN CREWS**

**Product # 2021**

**FOR PROFESSIONAL USE ONLY**  
 CONSULT LABEL AND MSDS BEFORE USING.

HMIS	
1	HEALTH
3	FLAMMABILITY
1	REACTIVITY
1	PROTECTION

INGREDIENTS	CAS #
DIPROPYLENE GLYCOL	
METHYL ETHER	34590-94-8
DIPROPYLENE GLYCOL	25265-71-8
DIMETHYL SULFOXIDE	67-68-5

**Additional Information**

**SAFE STRIP B** removes Graffiti, Paint & Varnish on Concrete, Brick, Cinder block, Wood, Metals, Glass, Plaster. Surface temperatures should be at 50°F to 95°F (10°C to 35°C). **SAFE STRIP B** performs effectively at lower temperatures, but the dwell time must be increased. Above 85°F (30°C), product may need to be over applied, re-applied or covered with plastic to prevent drying during dwell time. **SAFE STRIP B** will not strip novalac epoxies. Safety requirements Proper safety procedures should be followed at all times while handling this product. Refer to the Material Safety Data Sheet for important health/safety information before use. Do not collect and/or store removed paint and stripper waste residue in metal containers. Only use plastic containers. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation. **NOT APPROVED FOR AVIATION USE!!**

**ENVIRONMENTALLY FRIENDLY**  
**SAFE STRIP B**  
 Industrial Paint Stripper

**SAFE STRIP B**

**SAFE STRIP B** is a low VOC, water-based paint remover that will effectively lift epoxies, urethanes, lead based architectural coatings, and powder coatings. Recommended for use on nearly all substrates including steel, aluminum, concrete, masonry, wood, (lead based paints) or in any area where worker safety or damage to delicate equipment may be a concern. **SAFE STRIP B** contains no TAP's or Hap's, offers easy cleanup with soap and water or denatured alcohol. This technology utilizes physical energy to break the bond between the coating and the substrate, lifting the paint right off the surface. Clean up can be done by Vacuuming, Scraping or Pressure Washing.




**See Label for Complete Directions**

**DO NOT SHAKE. DRILL**  
**OR HAND MIX ONLY.**



Before



After