

SUPER COAT PRIMER is a sag-free primer that provides maximum rust and chemical protection. **SUPER COAT PRIMER** provides superior wear resistance and adhesion, and creates a strong base coat on bare metal and wood. Use with **SUPER COAT-A** High Solids Industrial Coatings.

SUPER COAT PRIMER

Professional Grade Primer Coating

- Fast Drying - Sag Free
- Excellent Hide - Interior/Exterior
- Sandable, Fade and Chip Resistant
- Provides Maximum Rust Protection
- Outdoor / Indoor Durability
- Use on Bare Metal and Wood Surfaces

Use On:

- | | |
|-------------|----------------------------|
| ·Metal | ·Fire Doors |
| ·Wood | ·Bins |
| ·Aluminum | ·Motors |
| ·Machinery | ·Tanks |
| ·Structural | ·Piping |
| Steel | ·Farm/Industrial equipment |
| ·Racks | |

Product: # 1431 Aerosol

DIRECTIONS FOR USE:

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10° C and 32° C).
2. Shake can at least on minute after rattle is heard and occasionally during use.



3. Spray surface with steady even strokes at a distance of 8 to 10 inches(20 to 25CM). Several light coats give a better finish than one heavy coat.

4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slots. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with gentle twisting motion.

5. To clear a prayhead for future use, turn can upside down for 3 seconds. Completely empty cans may be recycled or disposed of with

regular trash. Dispose of partially empty cans responsibly.

WARNING: This product contains a chemical known to the state of california to cause cancer, birth defects, or other reproductive harm.

Primer Paint Does Not Exceed 60% VOC or 1.20 MIR

AEROSOL HMIS	
1	HEALTH
4	FLAMMABILITY
3	REACTIVITY
	SPECIFIC

Additional Information

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION.

Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C).

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Vapors may ignite explosively. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights, turn off all stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breath dust, vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN