

The YES Company!!

**SUPERCO**  
SPECIALTY PRODUCTS

**TACKY**  
Super Penetrating  
Lubricant  
with TEFLON®

CONTAINS TEFLON® FOR  
INCREASED LUBRICITY  
HAS SUPER LEGS & TACKIFIERS  
PENETRATES HARD TO REACH  
AREAS  
LUBRICATES FOR EXTENDED  
PERIODS OF TIME

**Product # 1115**

**FOR PROFESSIONAL USE ONLY**  
CONSULT LABEL AND MSDS BEFORE USING.

**TACKY** Penetrating Lubricant is a super extreme pressure lubricant. **TACKY** contains Teflon® for extra long lasting lubricating abilities. **TACKY** is dispensed as a penetrant and gets into hard to reach areas and sets up within minutes to a heavy duty grease for long lasting lubrication. Teflon is a Dupont registered trademark.

**USE IN:**

Industry, municipalities, automotive, institutional, manufacturing, etc.

**USE AT:**

City buildings and facilities, schools, colleges, high-rise buildings, apartment complexes, factories, refineries, etc.



**DIRECTIONS FOR USE:**

Shake well before use. Remove protective cap and aim valve opening towards area to be lubricated. Saturate area. Use extension tube for hard to reach areas. Repeat as necessary.

1	HEALTH
0	FLAMMABILITY
1	REACTIVITY
1	PROTECTION

**INGREDIENTS**

HEXANE  
PROPANE  
ISOBUTANE  
PETROLATUM

**CAS NUMBER**

110-54-3  
74-98-6  
75-28-5  
801-29-51

## Additional Information

**TACKY** Super Penetrant is a very unique and highly specialized lubricant. **TACKY** is a clear, translucent color that is almost invisible, ideal for areas where red or black greases would be unsightly. **TACKY** shares many of the characteristics of high temp heavy lubricants such as superior adhesion, tackifiers (commonly referred to as "legs"), and high pressure additives. Good adhesion keeps the lubricant in place and prevents "fly-off" and dripping off. The tackifiers keep the grease "stringy", the process of transference which keeps the lubricant distributed onto both mating surfaces, to insure no metal-to-metal contact. High pressure additives allow the grease to remain in between two surfaces even under extreme pressures possibly reaching 50,000 to 100,000 pounds per square inch. Usually features such as these are only found in special bulk greases that have to be lubricated through special fittings. **TACKY** gives you the features you need in an aerosol spray that penetrates first into hard to reach spots then protects and lubricates for months.