

The YES Company!!

SUPERCO
SPECIALTY PRODUCTS

ACTIVATE-A

CITRUS BASED ORGANIC CLEANER & DEGREASER
TAR AND ASPHALT REMOVER
NON-CHLORINATED

- REMOVES OIL, GREASE, SLUDGE, AND TAR BUILD-UP FROM CONSTRUCTION VEHICLES, TRUCKS, OIL TANKERS, FUEL DELIVERY VEHICLES, ETC.
- CITRUS BASED CLEANING ACTION REMOVES TAR AND ASPHALT FROM BRICK, STONE, CONCRETE, AND OTHER MASONRY SURFACES
- CONTAINS NO HARSH ALKALI OR CORROSIVE INGREDIENTS ` NO CHLORINATED OR FLUORINATED SOLVENTS
- pH BALANCED
- 100% ENVIRONMENTALLY SAFE

Product # 1086 Aerosol

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

ACTIVATE A
TAR AND ASPHALT REMOVER

ACTIVATE-A is SUPERCO's environmentally safe and pH balanced organic formula powerful enough to instantly emulsify tar, asphalt, crude oil, grease, etc. without the hazards associated with most solvents.

- ACTIVATE-A degreases, deodorizes and cleans with unbelievable power and at the same time keeps up with today's environmental and safety regulations.



- USDA authorized for use in federally inspected meat and poultry plants.

- Use on motors, machinery, floors, paving equipment, vehicles, trailers, lifts, concrete tile, stone, dumpsters, trucks, busses, construction tools, tar applicators, etc.

- Used by maintenance personnel at highway departments, construction companies, oil refineries, industrial plants, food processing facilities, power companies, elevator service companies, utility companies, transportation authorities, military installations, municipal road crews, heavy equipment firms, etc.

HMIS	
1	HEALTH
2	FLAMMABILITY
1	REACTIVITY
1	PERSONAL

INGREDIENTS	CAS NUMBER
d-LIMONENE CITRUS TERPENE	5989-27-5
NON-IONIC SURFACTANT	25154-52-3
CARBON DIOXIDE	124-38-9

DIRECTIONS FOR USE:

Tar and Asphalt Removal: Spray ACTIVATE-A onto surface to be cleaned. Allow ACTIVATE-A to penetrate surface for 5 minutes before rinsing. Watch as ACTIVATE-A instantly starts dissolving tar and asphalt.. Rinse with water under pressure. Regular application of ACTIVATE-A is recommended for good maintenance practice.

Engine Degreasing: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes for complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.