

ACTI-VATE TAR AND ASPHALT REMOVER

The YES Company!!



ACTI-VATE
CITRUS BASED ORGANIC CLEANER & DEGREASER
TAR AND ASPHALT REMOVER
NON-CHLORINATED

- REMOVES OIL, GREASE, SLUDGE, AND TAR BUILD-UP FROM CONSTRUCTION VEHICLES, TRUCKS, OIL TANKERS, FUEL DELIVERY VEHICLES, ETC.
- CITRUS BASED CLEANING ACTION REMOVES TAR AND ASPHALT FROM BRICK, STONE, CONCRETE, AND OTHER MASONRY SURFACES
- CONTAINS NO HARSH ALKALI OR CORROSIVE INGREDIENTS • NO CHLORINATED OR FLUORINATED SOLVENTS
- pH BALANCED • 100% ENVIRONMENTALLY SAFE

PRODUCT #3055P PINT
PRODUCT #3055 QUART
PRODUCT #5165 BULK

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

- **ACTI-VATE** is **SUPERCO**'s environmentally safe and pH balanced organic formula powerful enough to instantly emulsify tar, asphalt, crude oil, grease, etc. without the hazards associated with most solvents.
- **ACTI-VATE** degreases, deodorizes and cleans with unbelievable power and at the same time keeps up with today's environmental and safety regulations.
- **USDA** authorized for use in federally inspected meat and poultry plants.



- **Use** on motors, machinery, floors, paving equipment, vehicles, trailers, lifts, concrete tile, stone, dumpsters, trucks, busses, construction tools, tar applicators, etc.

- **Used** by maintenance personnel at highway departments, construction companies, oil refineries, industrial plants, food processing facilities, power companies, elevator service companies, utility companies, transportation authorities, military installations, municipal road crews, heavy equipment firms, etc.

HMIS	
0	HEALTH
1	FLAMMABILITY
0	REACTIVITY
	SPECIFIC

INGREDIENTS

D-limonene

CAS#

5989-27-5

DIRECTIONS FOR USE:

Tar and Asphalt Removal: Apply undiluted to surface by spraying, mopping, or pouring. Allow **ACTI-VATE** to penetrate surface for 5 minutes before rinsing. Watch as **ACTI-VATE** instantly starts dissolving tar and asphalt.. Rinse with water under pressure. Regular application of **ACTI-VATE** is recommended for good maintenance practice.

Heavy Duty Cleaning: To remove heavy grease build-up on equipment or floors. Dilute product 1-10 with water and mix well. Apply liberally and let stand for 2-3 minutes, scrub thoroughly and rinse with water.

Engine Degreasing: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes for complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.