



# EZ-FILL

**Asphalt Road and Driveway Patching Compound**

**USED BY:**

- MUNICIPALITIES
  - CITIES
  - SCHOOLS
  - INDUSTRIAL PLANTS
  - PARKING LOTS
  - SPORTS COMPLEXES
- USE ON ANY ASPHALT ROADWAY**

**Product # 7006**

**FOR PROFESSIONAL USE ONLY  
CONSULT LABEL AND MSDS BEFORE USING.**

**EZ-FILL** is an extraordinary asphalt patching and filling compound that will long outlast conventional methods of repair while at the same time reducing labor costs. **EZ-FILL** is a finely ground material that compresses more than regular asphalt. This results in a much more solid repair that will withstand more traffic and ultimately last longer. **EZ-FILL** is easy, just fill the hole and tamp down. No need to oil the surface first and no curing is necessary. Roadways can immediately be opened to traffic.

**DIRECTIONS FOR USE:**

1. Surface should be clean of grease, oil and dirt. If extremely dusty, hose surface down with water. The surface need not be dry before application.
2. Remove **EZ-FILL** from container just as it is and place enough where needed allowing for sufficient compaction.
3. Pack down material with hand tamper or roller. If void is deeper than 1 inch, tamp material down in successive layers of 1 inch to assure maximum compression. No curing time is required. After 24 hours area may be sealed with **Superco Specialty Products EZ-SEAL**.

**INGREDIENTS**  
MINERAL SPIRITS

**CAS NUMBER**  
8052-41-3

1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
	SPECIFIC

<b>COMPOSITION</b>	%
NON-VOLATILE VEHICLE (ASPHALT SOLIDS).....	65%
VOLATILE VEHICLE (MINERAL SPIRITS).....	35%
	100%

## Additional Information

Asphalt repair can often be a repetitive process. You fill a pothole and before you know it water gets in, a few hundred trucks run over it, and now the hole is even bigger than before. Conventional asphalt is very coarse with gravel that averages 1/2 inch in diameter. No matter how hard you pack it moisture still penetrates and under the weight of traffic breaks apart the asphalt with hydraulic action. In cold weather this destruction is compounded by the water inside freezing and expanding on a daily cycle. **EZ-FILL's** fine texture allows for more compression providing a much harder, tighter patch that holds up under constant traffic for a greatly extended period of time. **EZ-FILL** can be used for repairing voids in asphalt, mastic or concrete pavements. For maximum longevity all asphalt roadways and repaired areas should be sealed with **Superco Specialty Products EZ-SEAL Asphalt Sealer**.

**SUPERCO SPECIALTY PRODUCTS**

VISIT OUR WEBSITE - [www.supercoproducts.com](http://www.supercoproducts.com) • Call Toll-Free (800)320-0102 • FAX (661)775-8884