



EZ-SEAL

Asphalt Black Top Sealer & Filler

- EASY TO APPLY
- EASY TO STIR
- ACRYLIC LATEX FORTIFIED ASPHALT COATING
- FILLS CRACKS UP TO 1/8" WIDE
- FILLS MINOR DEPRESSIONS UP TO 1/4" DEEP

Product # 5013

FOR PROFESSIONAL USE ONLY
CONSULT LABEL AND MSDS BEFORE USING.

INGREDIENTS **CAS NUMBER**
SILICA, CRYSTALLINE 14808-60-7

0	HEALTH
0	FLAMMABILITY
0	REACTIVITY
	SPECIFIC

EZ-SEAL Asphalt Driveway and Black Top sealer is an acrylic latex fortified driveway coating designed for application over all blacktop surfaces in sound condition. This product is formulated to fill and seal hairline cracks up to 1/8" wide. **EZ-SEAL** Driveway Coating provides an attractive and durable finish, and provides slip resistance on sloped surfaces.

DIRECTIONS FOR USE:

Surface Preparation: New blacktop should weather for 90 days minimum prior to coating. Surface to be coated must be clean and free of dust, dirt, oil, grease, etc. Remove grease and oil deposits with **Superco Specialty Products HURRICANE** diluted appropriately and rinsed with water. Cracks larger than 1/8" should be repaired using **Superco Specialty Products PLUG** Driveway Crack Sealer. Potholes and depressions should be filled with **Superco Specialty Products EZ-FILL**. Any repaired areas should be thoroughly cured prior to coating.

Application: **EZ-SEAL** Driveway Coating mixes easily. Some separation may occur and will require light stirring prior to use. Apply to cool, damp surface using a driveway brush. Spread coating thinly and evenly, working coating into cracks. Apply at 1 gallon per 100 sq. ft. (five gallons will cover approximately 500 sq. ft.). For best results, apply in the morning so the product has the full benefit of sunshine for proper curing. In hot weather, maintain damp surface during application. Dries to touch in 4 hours and can be open to traffic in 12 hours under normal conditions.

Additional Information

Asphalt driveways, playgrounds and roadways require maintenance just like any other part of a facility. Asphalt material being petroleum based, an oil product, deteriorates over time. Summer to winter cycles with the hot to cold temperature extremes are constantly breaking down the cohesion of asphalt surfaces, basically turning them into gravel. The best protection for your new and old asphalt is **EZ-SEAL** Driveway and Black Top Sealer. **EZ-SEAL** fills hairline cracks and slight depressions to give a nice smooth surface. **EZ-SEAL** will cover any discolorations, graffiti or unused stripes leaving a beautiful solid black color. Our premium quality formula provides slip resistance and excellent weather protection. Don't wait until your asphalt areas are falling apart and need to be replaced, keep them looking new year after year with **EZ-SEAL**.

SUPERCO SPECIALTY PRODUCTS

VISIT OUR WEBSITE - www.supercoproducts.com • Call Toll-Free (800)320-0102 • FAX (661)775-8884