

The YES Company!!
SUPERCO
 SPECIALTY PRODUCTS

PLUG
Asphalt Crack & Driveway Crack Filler
 PREVENTS PENETRATION OF MOISTURE

EASY POUR SPOUT FILLS CRACKS UP TO 1/2" WIDE

DRIES TO BLACK RUBBER HARD CONSISTANCY

ONE GALLON FILLS 200-225 LINEAL FEET @ 1/4" USE SUPERCO's EZ-SEAL

Product # 5124

FOR PROFESSIONAL USE ONLY
 CONSULT LABEL AND MSDS BEFORE USING.

PLUG
 Asphalt Crack & Driveway Crack Filler

This sealer is ideal for filling cracks 1/2 wide or smaller in any blacktop or concrete surface. **PLUG** dries to a black rubber-hard consistency, providing a crack-free surface. One gallon of **PLUG** fills 200 to 225 lineal feet of 1/4" x 1/4" cracks. Packaged in pourable one gallon jugs.

ADVANTAGES:

- Protects and prevents the penetration of moisture and freeze/thaw surface attack.
- easy to use - Easy pour spout - No tools necessary to fill cracks up to 1/2" wide.
- Dries fast - Apply **EZ-SEAL** sealer after 24 hours.

DIRECTIONS FOR USE:

Preparation: Surface must be clean and free of loose material, dirt and dust. Cracks and joints may be hosed clean, but remove standing water. Cracks over 1/2" deep should be partially filled with sand.

Application: Shake container before using. Do not thin with water. Keep pour spout tightly closed when not in use. Pour into crack, which can be damp but not wet, filling to slightly above the surface. Allow to harden before permitting traffic. Large cracks may require a second application.



INGREDIENTS **CAS NUMBER**
 FORMALDEHYDE 50-00-0

0	HEALTH
0	FLAMMABILITY
0	REACTIVITY
	PROTECTION

Additional Information

PLUG Asphalt Crack & Driveway Crack Filler is certainly the most convenient repair material to ever be developed. This advanced product requires no mixing, no brushes, no trowels, no machinery, no heating and no special training. **PLUG** pours directly out of the jug into cracks and crevices in both asphalt and concrete paving. To make the job easier and with less mess, we have included a special

pour spout. Deep cracks get filled with some sand first, but other than that **PLUG** is a one-step operation. Proper asphalt maintenance requires periodic resealing. Use **PLUG** 24 hours prior to sealing with **EZ-SEAL** for a "like new" smooth appearance on asphalt surfaces. **PLUG** is equally effective as a concrete crack sealer and provides better weather resistance than many other types of fillers. This product is the perfect solution for a company where the maintenance staff is generally busy and has limited time for these kinds of projects. For a demonstration of the ease of **PLUG** contact your local **Superco Specialty Products** representative.

SPECIFICATIONS:

Type: Asphalt Emulsion
 Weight per gallon (approx.): 9.3 lbs.
 Viscosity @ 80°F. (27°C.) (ASTM D562): 95-105 K.U.
 Drying times (approx.):
 For traffic: 6 daylight hrs.
 To touch: 15 minutes
 Color: Black
 % Solids by weight: 69-74%
 Water resistance: Excellent after curing.
 Freeze-Thaw stability: Yes

SUPERCO SPECIALTY PRODUCTS